



MODEL 1110

DC V AC V DC A Ω \bullet) $^{\circ}\text{C}$

- High sensitivity DC20k Ω /V
- 1m drop-proof heavy duty design
- Can measure line voltage up to AC 600V (Voltage to ground MAX AC 300V) (Protected by 600V ceramic fuse against accidental overload)
- Continuity buzzer, battery check, LED check function
- Skeleton type robust and clear case with carrying handle furnished as standard accessory

CE

	1110
DC V	0.3V(16.7k Ω /V) \pm 3% of FS 3/12/30/120/300/600V(20k Ω /V) \pm 3% of FS
AC V	12V(9k Ω /V) \pm 4% of FS 30/120/300/600V(9k Ω /V) \pm 3% of FS
DC A	60 μ A/30/300mA \pm 3% of FS
Ω	3/30/300k Ω \pm 3% of scale length
Continuity buzzer	Buzzer sounds below 100 Ω
Battery Test	1.5V(0.7 - 2V) \pm 3% of FS (10 Ω load)
Temperature	Possible with the temperature probe 7060 (discontinued).
LED	Approx. 10mA at 0 Ω (at 3V of battery voltage)
Applicable Standards	IEC 61010-1 CAT III 300V / CAT II 600V, IEC 61326-1
Power source	R6(AA)(1.5V) \times 2
Dimension	140(L) \times 94(W) \times 39(D)mm
Weight	Approx. 280g
Accessories	7066A(Test leads), 8923(Fuse[0.5A/600V]) \times 1 (included), 1 (spare) R6(AA) \times 2, 9103(Carrying case), Instruction manual

**COSINUS Messtechnik - Ihr Partner für Messlösung
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

office@cosinus.de
www.cosinus.de