

KEW 2300R

KEW FORK CURRENT TESTER

- True RMS
 - Ø10
 - MAX 100A
 - DC AC A
 - NCV
 - DATA HOLD
- AUTO POWER OFF

- True RMS reading is an essential feature for accurate measurement
- "Non Contact Voltage" function indicates the presence of AC voltage by warning the user with an audible signal
- Zero adjustment of DC current is possible at the push of a button
- Auto Power Off
- Minimum resolution 0.1A




KEW 2300R can be used in crowded connection boxes, where cables are very short, and space is too limited to clamp cables using a traditional clamp meter.


2300R	
Current measurement	AC A 0 - 100.0A ±2.0%rdg±5dgt [50/60Hz] DC A 0 - ±100.0A ±2.0%rdg±5dgt
Crest factor	2.5
Non contact voltage	Detect AC voltage without contacting with socket wire. During voltage detection, "Hi" flashes and a buzzer sounds.
Maximum digit	1,049
Conductor size	Max φ10mm
Applicable Standards	IEC 61010-1 CAT III 300V Pollution degree 2
Power source	R03 (AAA) × 2 (Auto power off : Approx. 10 minutes) *Continuous measuring time : AC A Approx. 46 hours DC A Approx. 52 hours
Dimension	161(L) × 40(W) × 30(D)mm
Weight	110g (including batteries)
Accessories	9113(Carrying case), R03 (AAA) × 2, Instruction manual

True RMS (Root Mean Square value) Measurement

Averaging Value



True RMS Value



Instrument Layout



**COSINUS Messtechnik - Ihr Partner für Messlösung
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

office@cosinus.de
www.cosinus.de