

## MODEL 2608A AC ANALOG CLAMP METER

- DC voltage range is also available especially for checking emergency battery operated power supply.
- Tear drop shaped transformer jaws for ease of use.



AC A	6/15/60/150/300A ±3% of FS
AC V	150/300/600V ±3% of FS
DC V	60V ±3% of FS
Ω	1/10kΩ (25/250Ω mid-scale) ±2% of scale length
Temperature	Note: The MODEL2608A includes a temperature measurement but it is not available for new customers due to the discontinue
Conductor size	Ø33mm max.
Frequency response	50Hz/60Hz
Applicable standards	IEC 61010-1 CAT III 300V Pollution Degree 2 IEC 61010-2-031 IEC 61010-2-032
Power source	R6 (AA) (1.5V) × 1
Dimension	193(L) × 78(W) × 39(D)mm
Weight	275g approx.
Accessories	7066A (Test leads) 8923 (Fuse [0.5A/600V]) × 2 9097 (Carrying case) R6 (AA) × 1 Instruction Manual

CE

**COSINUS Messtechnik - Ihr Partner für Messlösung  
in allen elektrischen und physikalischen Anwendungen**

**COSINUS Messtechnik GmbH**

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

[office@cosinus.de](mailto:office@cosinus.de)  
[www.cosinus.de](http://www.cosinus.de)