

KEW 4300

SIMPLIFIED EARTH TESTER



CE

4300	
Earth resistance ranges	200.0/2000Ω(Auto-ranging) ±3%rdg±5dgt
Voltage ranges	AC:5.0 - 300.0V(45 - 65Hz) ±1%rdg±4dgt DC:±5.0 - 300.0V ±1%rdg±8dgt
Applicable Standards	IEC 61010-1 CAT III 300V pollution degree 2 IEC 61557-1,5 IEC 61326-1,2-2, IEC 60529(IP40)
Power source	LR6(AA)(1.5V) × 2
Dimension	232(L) × 51(W) × 42(D)mm
Weight	Approx. 220g(including battery)
Accessories	7248(Test lead with Alligator clip and Flat test probe) 8072(CAT II Standard prod) 8253(CAT III Standard prod) 8017(Extension prod long) 9161(Carrying case) Instruction manual, LR6(AA) × 2

KEW 4300 is simplified earth resistance tester (based on 2-pole method) that can be used for various distribution lines and electrical appliances and it also can measure AC/DC voltage. (As for AC voltages, True RMS values can be obtained.)

- 200/2000Ω (2 ranges) : Auto-ranging
- Warning buzzer triggered at 100Ω or less
- LED lights up when a large earth voltage is detected
- Live circuit warning when 30V or higher voltage is detected (KEW 4300 detects voltage even when measuring resistances)
- LED light for illuminating measurement points (It turns on/off automatically in relation to the ambient brightness)
- Small test current (max 2mA) not tripping RCD

Accessories/Optional Accessories /Related Products



**COSINUS Messtechnik - Ihr Partner für Messlösung
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

office@cosinus.de
www.cosinus.de