

RCD TESTERS

MODEL 5406A



- Custom microprocessor controlled for highest accuracy and reliability
- 3 LEDs for checking correct wiring status
- 0 and 180 degree phase angle switch permits quick tests and consistent readings
- Digital read-out of tripping time
- Test of a large kind of RCDs : Standard, Selective, AC and A(DC sensitive breakers)
- Constant current source circuitry ensures that a fluctuating mains voltage does not affect the accuracy of readings
- Large custom digital display readout
- Visual indication of reversed phase and neutral wiring at socket
- Designed to IP54 Rating
- Complies with IEC 61557

	5406A
Rated tripping current	10/20/30/200/300/500mA
Fault condition settings	× 1/2 × 1 × 5 × DC Auto Ramp
Trip current duration	1000ms 200ms(× 5)
Lowest resolution	1ms
Trip time accuracy	±0.6%rdg±4dgt
Operating voltage	230V+10-15% (195 - 253V)[50Hz]
Applicable Standards	IEC 61557-1,6 IEC 61010-1 CAT III 300V Pollution degree 2 IEC 61010-031 IEC 60529(IP54)
Dimension	167(L) × 186(W) × 89(D)mm
Weight	Approx. 800g
Accessories	Molded plug test lead*1, 9147(Cord case) 9121(Shoulder strap), Instruction manual
Optional Accessories	7121B(Distribution board test leads)

*1 7123(AU) : Australian plug 7124(UK) : British plug(13A)
7125(EU) : European SCHUKO plug 7126(SA) : South african plug

Accessories

Molded plug test lead



MODEL 7123
(AU)Australian plug

MODEL 7124
(UK)British plug(13A)

MODEL 7125
(EU)European SCHUKO plug

MODEL 7126
(SA)South african plug

Optional Accessory



MODEL 7121B
Distribution board test leads

**COSINUS Messtechnik - Ihr Partner für Messlösung
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

office@cosinus.de
www.cosinus.de