

CLAMP SENSOR

KEW 8115

CLAMP SENSOR



8115	
Measuring range	AC 0.1 - 130Arms DC 0 - ±180A
Output voltage	AC 10mV/A DC 10mV/A
Accuracy	±1.2%rdg±0.4mV (50/60Hz) ±2.5%rdg±0.4mV (40Hz - 1kHz) ±1.2%rdg±0.4mV (*)
Low battery warning	2.2V±0.2V or less - Red LED flash (1.9V±0.2V - Automatically power off)
Conductor size	φ12mm max.
Operating temperature & humidity range	-10 - 55°C, relative humidity 85% or less (no condensation)
Output impedance	Approx. 10Ω or less
Applicable Standards	IEC 61010-1 CAT III 300V Pollution degree 2, IEC 61010-2-032, IEC 61326-1
Power source	LR03(AAA)(1.5V) × 2 Continuous use: Approx. 40 hours(Auto power off: Approx. 20 minutes)
Cord length	Approx. 1,200mm
Output connector	φ4mm banana plug
Dimension	127(L) × 42(W) × 22(D) mm
Weight	Approx. 140g
Accessories	9095(Carrying case), LR03(AAA) × 2, Instruction manual

*This accuracy is defined after the completion of zero adjustment under connection to a DMM.

- Clamp sensor for AC/DC current measurement compatible with digital multimeters

**COSINUS Messtechnik - Ihr Partner für Messlösung
in allen elektrischen und physikalischen Anwendungen**

COSINUS Messtechnik GmbH

Rotwandweg 4

82024 Taufkirchen

Tel.: 089 / 66 55 94 - 0

Fax: 089 / 66 55 94 -30

office@cosinus.de
www.cosinus.de